



# Zebra® TTP 7000 Series™ Kiosk Printers



SEE MORE. DO MORE.



The TTP 7030 is a fast, reliable and versatile kiosk printer specially designed for unattended operation. It's built to work in harsh environments such as heat, cold and vibration. And with the jam-preventing loop presenter, guillotine cutter and pull detector, the TTP 7030 provides trouble-free operation. The only maintenance required is to replace the media roll. The TTP 7030 can support 3.15"/80 mm to 4.4"/112 mm media

widths, plus a wide printing format that provides room for extensive information or graphics, allowing Web or A4 pages to be downscaled into pocket format. When connected via USB interface, the printer is plug-and-play compatible with Windows®, or the printer can be addressed directly from the kiosk software in text mode. The TTP 7030 has Flash memory to store large downloaded files like fonts and graphics.

## TTP 7000 Series Kiosk Printers Offer:

### Unremitting Reliability to Keep Kiosks Printing

Optimized for tough printing environments where durability, reliability, minimal maintenance and ease of use are critical, Zebra printers maximize uptime and minimize upkeep.

### Easy to Integrate in Kiosk Designs

A small footprint and flexible mounting options make our printers ideal for a variety of applications.

### End Benefits

As an integral part of a self-service kiosk solution, Zebra printers help companies improve service, raise customer satisfaction, increase revenue and lower operational costs.

# SPECIFICATIONS AT A GLANCE\*

## Printer Name

TTP 7030/80  
TTP 7030/112

## Standard Features

- Direct thermal receipt and document printing for 3.15"/80 mm or 4.4"/112 mm width media
- Looping presenter with pull detector
- Retract & retain function optional
- Auto media loading
- Various media mounting options behind and below give flexibility to kiosk design, up to 9.8"/250 mm diameter media rolls
- USB connectivity
- 203 dpi printing
- Windows® drivers for plug and play
- Prints any font, code page, barcode and graphics supported by the operating system



## Printer Specifications

### Resolution

203 dpi/8 dots per mm

### Maximum Print Width

- 2.8"/72 mm (TTP 7030/80)
- 4.1"/104 mm (TTP 7030/112)

### Maximum Print Length

23.6"/600 mm

### Print Speed

3"/75 mm per second

### Media Sensors

Out-of-paper, black mark, paper in presenter, pull detector, and paper-low reporting

## Media Characteristics

### Maximum Paper Length

23.6"/600 mm

### Paper Width

- 3.1"/80 mm (TTP 7030/80)
- 4.4"/112 mm (TTP 7030/112)

### Maximum Roll Size

9.8"/250 mm

### Media Thickness

0.002"/0.054 mm to 0.005"/0.13 mm

### Media Types

Roll or fanfold paper

## Operating Characteristics

### Environmental

- Operating Temp.: 23° F/- 5° C to 104° F/40° C
- Storage Temp.: 14° F/-10° C to 122° F/50° C
- Operating Humidity: 35% to 75% non-condensing
- Storage Humidity: 10% to 90% non-condensing excluding paper

### Electrical

- TTP 7030/80: 24Vdc +/-10% average 2.5A, peak 8.5A
- TTP 7030/112: 24Vdc +/-10% average 3.5A, peak 11A

## Physical Characteristics

### TTP 7030/80

- Width: 5.4"/136 mm
- Height: 5.6"/141 mm
- Depth: 5.9"/150 mm
- Weight: 5.3 lbs/2.4 kg

### TTP 7030/112

- Width: 6.6"/168 mm
- Height: 5.6"/141 mm
- Depth: 5.9"/150 mm
- Weight: 6.3 lbs/2.9 kg

## Fonts/Graphics/Symbologies

### Barcodes

EAN 8 and 13, UPC, Interleaved 2-of-5, ISBN, Code 39 and Code 128

### Graphics

Logotypes and b&w BMP-files

### Standard Fonts

ATM9 (Monospaced 14.4 cpi), up to 8 fonts can be uploaded

### Text Attributes

Underline, bold, italics, reverse print, multiple width and height

## Communication and Interface Capabilities

- USB (standard)
- Serial RS232 adapter (optional)

## Operating System

Windows 2000, XP, Server 2003 and OPOS

## Options and Accessories

- Retract & retain function
- 3.1"/80 mm Roll Holder Behind with paper-low sensor, 5.9"/150 mm diameter max
- 3.1"/80 mm Roll Holder Below with paper-low and weekend sensors, 9.8"/250 mm diameter max
- 4.4"/112 mm Roll Holder Behind with paper-low sensor, 5.9"/150 mm diameter max
- 4.4"/112 mm Roll Holder Below with paper-low and weekend sensors, 9.8"/250 mm diameter max
- Paper-low and weekend sensors with 15.7"/400 mm cable
- RS232 serial interface adapter



**Corporate Headquarters**  
+1 800 423 0442  
inquiry4@zebra.com

**Asia-Pacific Headquarters**  
+65 6858 0722  
apacchannelmarketing@zebra.com

**EMEA Headquarters**  
+44 (0)1628 556000  
mseurope@zebra.com

**Latin America Headquarters**  
+1 847 955 2283  
inquiry4@zebra.com

**Other Locations / USA:** California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam **Latin America:** Argentina, Brazil, Colombia, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

\*Specifications subject to change without notice.

©2013 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. All rights reserved. Windows and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.

P1021844 (04/13)