

# AXR® 600

SUPER PREMIUM - RESIN  
FOR CORNER EDGE & NEAR EDGE

THERMAL TRANSFER RIBBONS

AXR® 600 is dedicated to applications requiring perfect printing quality and excellent mechanical resistances.

The ink provides excellent print quality of all types of barcodes, very small text, large characters and logos, at a blackness up to 1.8 (ODR).

The ribbon structure allows printing on many kinds of synthetics (PVC, PET, PE, PP) and on various matt and glossy coated papers.

The printed image offers an excellent smudge and scratch resistance and good heat resistance, up to 180°C.


Those characteristics remain at speeds up to 250 mm/s (10 ips) and with 200, 300 and 600 DPI printheads, making this ribbon perfectly adapted to the labelling market and allowing its use in the flexible packaging printing market.

AXR® 600 grade features ARMOR's outstanding backcoat technology, ensuring excellent printhead protection, preventing clogging and static build-up.


- ▶ EXCELLENT RESISTANCE TO SMUDGE AND SCRATCH
- ▶ EXCELLENT PRINTING QUALITY, SENSITIVITY AND RECEPTOR MULTI-COMPATIBILITY
- ▶ GOOD RESISTANCE TO HIGH TEMPERATURE

## PRINTING QUALITY


**Blackness**  
Macbeth D19C




**0°Barcode**



**Sharpness**




**90°Barcode**



## SENSITIVITY


**Printing Speed**



**Receptor Compatibility**

Uncoated papers	—
Coated papers	■
High gloss papers	■
Synthetics	■ ■


**Energy**




## RESISTANCES

**Mechanical Resistances**

Crockmeter, 680 g/cm<sup>2</sup>,  
no damage after 200 cycles.



**Heat Resistance**



**Other Resistances**



Rubtester: 939g, no damage after ... cycles :

IPA:	5	Ethanol:	5
Mineral Spirit:	30	Unleaded gasoline 98:	nr*
Motor oil:	250	Brake fluid:	nr*

\* not recommended

Evaluation of observed performances of the ribbon with optimised printer settings and receptors [ARMOR procedure].

# AXR<sup>®</sup> 600

SUPER PREMIUM - RESIN  
FOR CORNER EDGE & NEAR EDGE

THERMAL TRANSFER RIBBONS

## COLOUR RANGE

Data exposed in this sheet are for the black ribbon. Printing performance of the colour ribbons are close to black ones.



Black



White



Dark Blue  
(286 C)



Dark Red  
(485 C)



Light Green  
(Green C)

## ▶ EXAMPLES OF APPLICATION FIELDS

The characteristics of AXR<sup>®</sup> 600 answer the requirements of the following application fields:  
(If your application is not among the ones below, please contact us.)



Inventory




Shipping



Pharmaceutical



Cosmetics



Flexible Packaging



Flexible Packaging for frozen applications



Flexible Packaging for hot processes




Retail labeling



Rating plates



Care labels



Signage & Logos



Laboratory



Healthcare



Tags



Food contact



Livestock



Outdoor applications



Conveyor sorting



Chemical drums



Automotive

## ▶ CERTIFICATIONS AND APPROVALS

**Food contact:** This ribbon is compliant with the European Directive 1935/2004/EC.

**UL Approved:** Legibility and durability of the printed label.

**Heavy metals:** The ribbon is compliant with EC 95/638. SGS reports available upon request.

**RoHs/WEEE:** EC directives 2002/95 and 2002/96, compliance to the limitation of dangerous substances in electric and electronic equipments.

**REACH:** As a European manufacturer, ARMOR is completely fulfilling REACH requirements. Our ribbons are free from the Substances of Very High Concern (SVHC).

**CP65:** The ribbon is free from the substances listed.

**Halogen:** this ribbon is halogen free.


Contact us for all other regulations linked to product compliance with toxicity, treatment of wastes, banned components, packaging, etc.

## ▶ RIBBON SPECIFICATIONS

Backcoating →

PET film →

Ink layer(s) →



**Backcoating:**

Silicon based.  
Friction coefficient:  $K_d < 0.2$ .

**PET film:**

Thickness: 4.5  $\mu\text{m}$ .  
Tearing resistance:  $> 300 \text{ N/mm}^2(\text{MD})$ .

**Ink:**

Resin.  
Melting point: 80°C  
(ARMOR procedure).


**Ribbon:**

Thickness (black):  $< 9 \mu\text{m}$ .  
The ribbon is anti static build-up treated.  
Storage: 12 months, 5-35°C (40-95°F),  
20-80 % Humidity Rate.

## SUSTAINABLE DEVELOPMENT

ARMOR evaluation of AXR<sup>®</sup>600:

To be compared with our other products.



The film is produced in one of the industry's most organised and awarded factories:

**DECAPLAN:**

Sustainable development action plan based on 10 leading topics involving all profiles of the company.



**Global Compact:**

UNO initiative inviting companies to apply fundamental ethical and environmental values.



**Responsible Care:**

International Council of Chemical Associations' charter towards constant improvements in health, safety and environment.



**Quality, health, safety and environment certifications:**

ISO 9001 : 2008, N°QUAL/2007/28312  
ISO 14001 : 2004, N°ENV/2007/28315  
OHSAS 18001 : 2007, N°SMS/2007/28316



**AF AQ 1000NR (means millennium):**  
Evaluation of companies' state of advancement in sustainable development. ARMOR,  
1<sup>st</sup> company to reach "Exemplary" level.

