

QuickScan[®] QS6000 Plus

Handheld Scanner



Ideal for:

- Retail Applications
- Health Care
- Inventory
- Office Automation
- Light Industrial

Features:

- Great depth-of-field
- AutoSense[®] stand for hands-free operation
- Optional EAS antenna for simultaneous scanning and security tag deactivation
- Universal wedge for additional keyboard emulation, bar code symbologies and data editing

Check Out The Handheld Scanner That Sets The Standard For General Purpose Applications.

Great Performance At A Great Price!

The QuickScan[®] QS6000 Plus handheld scanner offers great performance at a very affordable price. With a high first pass read rate and the best speed-to-read of any scanner in its class, the QS6000 Plus speeds retail checkout and other general applications.

This high performance laser scanner offers extended depth-of-field, allowing the user to read labels at distances of 20" (50 cm) and beyond. Plus, PSC's advanced electronics perform well even when reading low contrast labels with poor edge definition.

Hardened for Tough Environments

The QS6000 Plus scanner incorporates the most advanced, high durability features available today. The reading engine and optics are protected by anti-shock mounts built to absorb up to 1500 Gs. In fact, the QS6000 Plus can withstand repeated five-foot drops to concrete.

The QS6000 Plus also features a strong, plastic enclosure that guards against liquid and dust infiltration. A tough, rubber-like shield cushions the scanner when dropped, protects the scan window from scratching and prevents the scanner from slipping off counter surfaces.

Lightweight & Ergonomic For Maximum Scanning Comfort & Productivity

The QS6000 Plus scanner was developed with operator comfort in mind—a critical factor that ensures prolonged operator productivity. The weight of its evenly balanced design can be held easily in any size hand, even during extended periods of use. When resting on a horizontal surface, in a stand, or in a belt holster, the handle is quickly and easily grasped for "scoop and scan" simplicity.

The QuickScan[®] QS6000 Plus: An Outstanding Value

With the QS6000 Plus scanner, there's no need to make trade-offs between quality and affordability. High-end performance, advanced ergonomic design, enhanced durability—the combination of these features in the QS6000 Plus adds up to one of the best values in the industry.



Specifications

QS6000 Plus

Mechanical

Dimensions: 6.5 x 2.8 x 4.2" /
16.5 x 7.1 x 10.7 cm

Weight

Scanner: 6.5 oz. / 184 g (scanner)

Optical

Light source: Visible Laser Diode (VLD), 650 nm

Scan system: Electromagnetic dithering mirror

Rate: 42 scans/sec. (nominal)

Depth-of-field: Refer to chart on this page

Resolution: 5 mils / 0.13mm

Print contrast ratio: 30% minimum

Pitch: ±65°

Skew: ±55°

Scan angle: 46°

Ambient light immunity

Artificial light: 1,200 foot candles / 12900 Lux

Sunlight: 8,000 foot candles / 86100 Lux

Electrical

Operating voltage

Undecoded: 4.2 V to 14 VDC

Decoded: 4.5 V to 14 VDC

Operating current - nominal

Undecoded: 70 mA to 5 VDC

Decoded: 120 mA to 5 VDC

Idling current - nominal

Undecoded: 10 µA to 5 VDC,

Decoded: 23 mA to 5 VDC;

Decoded, lowest power mode: 14 mA to 5 VDC

Environmental

Temperature

Operating: 32° to 122° F / 0° to 50° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Shock (at 23°C): Withstands multiple 5.0' / 1.5 m drops onto concrete / 100+ drops to countertop

Vibration: MIL-STD-810E

Decoding Capability

- UPCA, E / EAN 8,13 / JAN 8, 13
(Codes add-ons P2 / P5, Code 128)
- Code 128/EAN 128
- Pharmacode 39
- Interleaved 2/5
- Code 39
- RSS on selected models
- Codabar
- Code 93
- Standard 2/5, IATA
- MSI/Plessey

Communications

Single and dual interface models

- RS232
- Standard Keyboard Wedge
- Universal Keyboard Wedge
- IBM 46XX
- USB
- Wand Emulations
- OCIA
- Undecoded

Safety & Regulatory

Electrical: Complies to: Gost R; TÜV; UL; cUL

Emissions: Complies to: FCC-A; EN 55022-B;

BCIQ CNS 13438; AS/NZS 3548; VCCI-B

Laser classification: CDRH Class IIa ;

(ATTENTION: Laser Radiation - do not stare into beam); IEC 60825 Class 1 & 2



Depth-of-Field	
Printing resolution, contrast and ambient light dependent	
Label Density	Range
5 mil	1.0 to 3.0" / 2.5 to 7.6 cm
7.5 mil	0.5 to 6.0" / 1.3 to 15.2 cm
10 mil	0.0 to 9.0" / 0.0 to 22.9 cm
13 mil	0.0 to 13.0" / 0.0 to 33.0 cm
20mil	up to 20.0" / up to 50.8 cm

Available Mount Options



P/N: 7-0204
AutoSense®

P/N: 7-0470
AutoSense®
(w/o base)

P/N: 5-0788
Universal Holster

P/N: 7-0393
Mountable
Tabletop



This product is manufactured in the United States and Singapore.

PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

Specifications are subject to change without notice.

Additional information concerning this product or other PSC products and services can be found at the PSC website: www.pscnet.com, or contact your PSC representative for more information.



PSC Worldwide Sales and Service locations

Australia - NSW
Tel: 61 2 9878 8999
Fax: 61 2 9878 8688

Belgium
Tel: 32 2 414 74 09
Fax: 32 2 410 11 63

Brazil
Tel: 55 11 5507 7721
Fax: 55 11 5507 7696

Chile
Tel: 562-339-7000
Fax: 562-339-7985

China
Tel: 86 10 6857 9048
Fax: 86 10 6857 8699

China - South
Tel: 86 20 8765 9955
Fax: 86 20 8765 9955

France
Tel: 33 1 64 86 71 00
Fax: 33 1 64 46 72 44

Germany
Tel: 49 6151 93580
Fax: 49 6151 935897

Hong Kong
Tel: 852 25846210
Fax: 852 25210291

India
Tel: 91 11 24621586
Fax: 91 11 24641662

Italy
Tel: 39 039 629031
Fax: 39 039 6859496

Japan
Tel: 81 3 3491 6761
Fax: 81 3 3491 6656

Latin America
Tel: 1 305 539 0111
Fax: 1 305 539 0206

Singapore
Tel: 65 435 1311
Fax: 65 226 1242

Spain
Tel: 34 91 746 28 60
Fax: 34 91 742 35 33