

Keyfob " Drop "

iDTRONIC keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal key ring. They are available with the most common ICs in 125kHz as well as in 13,56MHz.



Applications:

- Access Control

Personalisation options:

- Laser engraved serial number
- Printed logo

Product specification:

Dimensions:	53 x 33 x 4mm
Weight:	7g
Material:	Polycarbonat
Colours:	black, blue, red, green, yellow
Surface:	opac
Application temp. :	- 25°C to 65°C

Available 125kHz systems:

IC Type	Memory	Mode	Anticollision	Antenna	Order No.
EM 4100	64 bit	Read Only	No	Wire	KF-D-4100
EM 4550	1024 bit	R/W	No	Wire	KF-D-4550
Atmel Temic 5567	224 bit	R/W	Yes (AOR)	Wire	KF-D-5567
NXP Hitag 1	2048 bit	R/W	Yes	Wire	KF-D-HT1
NXP Hitag 2	256 bit	R/W	No	Wire	KF-D-HT2

Available 13,56MHz systems:

IC Type	ISO	Memory	Anticollision	Antenna	Order No.
NXP Mifare MF1S50	14443A (1-3)	1024 byte	Yes	Wire	KF-D-MFS50
NXP I-Code SLI	15693	1024 bit	Yes	Wire	KF-D-ICSLI
STM SR 176	14443B	176 bit	Yes	Wire	KF-D-SR176
Legic MIM 256	-	256 byte	No	Wire	KF-D-MIM256

Other IC types available on request!