

Za tehnično podporo ali pomoč pokličite  
**090-6009**

## Unitech EA300 Specifications Guide



Več informacij: <http://www.info-kod.si>

---

Vprašanja? Kontaktirajte naše strokovnjake



090-6009



servis@info-kod.si



<http://www.info-kod.si>

Ponedeljek – Petek od 9:00 do 15:00





# EA300

## 4" Rugged Android Computer with keypad.

The Unitech EA300 (Android 5.1) is a rugged 4" mobile enterprise computer combining wireless communication and performance to provide powerful data collection. The EA300 offers a host of data collection options to enhance the service level for a variety of vertical applications such as retail, inventory management, asset tracking, light warehousing.

### Powerful data entry and collection

The EA300 is designed with "intensive data entry a data collection" in mind. This device has a 4" TFT-LCD HD touch screen and features an integrated 17-key keypad (incl. alpha/numeric, scan keys and special characters) as well as dual scanning buttons (left and right side) for convenient barcode capturing.

In addition the EA300 offers an integrated 2D imager, GPS, 5.0 MP camera, HF/NFC RFID reader/writer to complete your data collection requirements. This device offers everything you'll need.

### All-in-one Functionality

Equipped with an 1.2GHz Quad-Core processor and running on the Android 5.1 operating system, making this device suitable for data-intensive applications in highly mobile environments. Mobile workers can easily accelerate their workflow as this device is equipped with a 2GB RAM, 16GB ROM and supports an additional microSD expansion (up to 32GB storage capacity).

Holding a 3800mAh removable battery the EA300 provides continuous usage time without needing to worry about running out of juice. Enjoy the fastest data speeds out there with the integrated Bluetooth 4.0, Dual-band 802.11 a/b/g/n WiFi and 4G LTE connectivity. This device is truly an excellent mobility device and offers job improvement and efficiency at a competitive price!

### Rugged design

Capable to withstand multiple 1.5m drops to concrete and IP65 rated against water and dust, makes this EA300 a rugged device. Equipped with a POGO PIN (for quick and non-intrusive charging) it will prolong life span and durability.



### Combining touch screen and keypad.

The 4" EA300 features a keypad, 2D imager, 4G LTE, Dual-band WiFi and comes standard with charging cradle!

### Main features

- All-in-one box; EA300 comes with USB cradle and power supply.
- All-in-one function: Keypad, 2D Imager, HF/NFC and 8MP Camera.
- Industrial grade: 1.2GHz Quad-Core processor with Android 5.1 OS
- Suitable for any mobile worker: 4G / LTE, Dual-Band 802.11 a/b/g/n WiFi, GPS and Bluetooth 4.0 HS slow energy.
- Rechargeable and swappable 3800mAh battery.
- 4" HD display touch screen and 17-key keypad.
- Rugged: Gorilla Glass 3, IP65 rated and 1.5m drop specification.
- Dual Scanning Buttons (left and right side) and scanning button on keypad.
- Device supported versatile: SOTI, 12Manage.
- Optional additional UnitCare 2.0 coverage available.

**unitech**  
because we care



# v1 EA300

## Specifications

### Operation System

|           |   |
|-----------|---|
| CPU       | 1.2GHz, Qualcomm 8916 Quad-Core   |
| Memory    | 2GB DDR RAM<br>16GB ROM   |
| OS        | Android 5.1<br>Enhanced security by preventing 3rd party data collection. |
| Languages | Multi-language  |

### Display

4" Gorilla Glass 3 touch screen. TFT-LCD HD (480 x 800) color.

### Buttons

|        |   |
|--------|---|
| Front: | 17 physical keys including Alpha/numeric, scan keys and special characters.   |
| Side:  | SCAN button x 2 (Left / Right), User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button. |

### Camera/Photos/Video

5MP rear camera with LED flash and auto-focus function

### Indicator

LEDs, Vibrator

### Symbologies

**2D CMOS Imager** (Honeywell N6603)  
1D/2D All major 1D and 2D codes

### RFID

HF/NFC Frequency 13.56MHz  
Support: ISO14443A/B, ISO15693 standard,  
Supports NFC

### Communication

|           |  |
|-----------|--|
| USB       | Micro USB  |
| OTG       | Yes, over Micro USB  |
| POGO PIN  | Charging via cradle and USB client                                     |
| WLAN      | 802.11 a/b/g/n   |
| Bluetooth | Bluetooth 4.0 HS low energy  |
| WWAN      | 4G TDD/FDD/UMTS/EV-DO/GSM<br>TDD-LTE (B38/B39/B40/B41) FDD-LTE (B1/B3) |
| GPS       | GPS, AGPS, Glonass   |
| Sensors   | Proximity sensor, light sensor and G-sensor                            |

### Power Source

|                |   |
|----------------|---|
| Main battery   | Rechargeable and swappable<br>3.8 V, 3800mAh Polymer Li-ION pack. |
| Operation time | 10-12 hours (depending on the specific environment)               |
| RTC battery    | Real time clock battery   |

### Unitech Europe

Tilburg, The Netherlands  
• Tel.: +31 (0)13 460 9292  
• Email: Info@eu.ute.com  
• Website: http://eu.ute.com

Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan

Specifications subject to change without notice. Copyright 2011, Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

### Audio

Microphone, speaker and 3.5mm audio jack

### Expansion Slot

Micro SD/TF x 1 (maximum of 32 GB), Micro SIM x 1, SAM x 1

### Enclosure

|           |                        |
|-----------|------------------------|
| Dimension | 152 mm x 78 mm x 30 mm |
| Weight    | 310g                   |

### Environmental

|                       |                           |
|-----------------------|---------------------------|
| Operating temperature | -10°C to +50°C            |
| Storage temperature   | -20°C to +60°C            |
| Charging Temperature  | 0°C to 40°C               |
| Relative Humidity     | 5% ~ 95% (non-condensing) |
| Drop Specification    | 1.5m to concrete          |
| Sealing               | IP65                      |

### Accessories

Single slot USB cradle



#### EA300 1-Slot Charging USB Cradle

1-slot USB cradle with spare battery\* charging compartment.

|         |                               |
|---------|-------------------------------|
| Input:  | AC 100V~240V, 1A Max, 50/60Hz |
| Output: | DC 5.5V, 2.6A                 |
| Led:    | Power and Status              |

\*NOTE: Second battery not included.

### Regulatory Approvals

CE, RED

### Device supported MDM

SOTI, 12Manage

### Warranty

1 Year Terminal and cradle / 3 months battery.



### Unitech's service program

UnitCare 2.0 offers customers a high level of security by a reliable, high-quality and effective program for getting your devices serviced quickly. It also drives the hidden costs out of your installations. Unitech goes beyond the standard warranty with a complete service offer for different need. **More information: [unitcare.unitech.eu](http://unitcare.unitech.eu).**

**unitech**  
because we care