

Info-Kod d.o.o., PE:Gerbičeva 110 Ljubljana 1000, Slovenija T: +386 1 256 24 99 F: +386 1 256 24 98 E: info@info-kod.si www.info-kod.si

Za tehnično podporo ali pomoč pokličite 090-6009



Unitech EA602 Brošura

Več informacij: <u>http://www.info-kod.si</u>

Vprašanja? Kontaktirajte naše strokovnjake



090-6009



servis@info-kod.si



http://www.info-kod.si

Ponedeljek – Petek od 9:00 do 15:00

unitech



EA602 Rugged Mobile Computer

The EA602 zooms to the head of the class with style, efficiency, and value. Run applications smoothly while on the road or in the office and scan simply with dual scan buttons for left- and right-handed users. The EA602 is powerfully portable and ideal for logistics, transportation, and field service verticals.

Intelligent

Powered by an Android 7.1 OS and a 1.4GHz Octa-Core processor, the EA602 delivers fast and reliable operations, proving it's what's inside that counts.

Easy on the Eyes

A sleekly designed body that molds into the palm of your hand and a 5-inch screen that's fully capacitive to show off images in high resolution make the EA602 a clear choice.

Tough as Nails

The EA602 can take a little bullying, and then some. An IP65 rating for environmental protection, 5-foot drop spec, and POGO pin charging makes for mighty data collection.

Well Connected

The EA602 moves in the right circles with its multiple access points. Connect to its Bluetooth 4.1, 4G, or WiFi dual-band 802.11 a/b/g/n/ac technology.

Not compromising form or function, the EA602 offers a slew of other features. An integrated HF/NFC RFID reader/writer, GPS, and high resolution 8MP camera makes capturing data a snap.

Main Features:

Well Rounded

- All-in-one box with USB cradle and power supply
- Android 7.1 operating system
- 1.4GHz Octa-Core processor
- Integrated 2D barcode scanner
- 5" HD ultra sensitive capacitive touch screen
- 8 MP autofocus rear camera / 2 MP front camera
- Dual band antenna connectivity (WLAN/WWAN)
- IP65 rated
- 5-foot drop rated



unitech

System CPU

Memory

Others

Display

Buttons

Software

1D/2D

RFID

Symbologies 2D CMOS Imager

Supported Languages

FA6()2 **Specifications**



Single Slot USB Cradle

Environmental

Operating temperature Storage temperature Charging temperature Relative humidity Drop rating Environmental seal Vibration and Shock test

14°F to 122°F (-10°C to 50°C) -4°F to 158°F (-20°C to 70°C) 0°C to 40°C 5% ~ 95% (non-condensing) 6 feet MIL-STD 810G IP6.5 5 ft (1.5m) to concrete

2MP front camera 8MP rear camera with LED flash and auto-focus function Micro SD/TF x 1 (maximum of 32 GB), Micro SIM x 1, SAM x 1 Micro USB 802.11 a/b/g/n/ac Bluetooth 4.1 LE GSM/HSDP+/UMTS, 4G FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B20/ B28A/B28B) 3G UMTS/HSDPA/HSPA/HSPA+ (850, 900, 1900, 2100 MHz) 2G GSM/EDGE/GPRS (850, 900, 1800, 1900 MHz) Charging via USB cradle and power supply Yes, over Micro USB Proximity sensor, light sensor and G-sensor LEDs, vibrator

Accessories

Single slot USB cradle

Regulatory Approvals CE, R&TTE



Specifications subject to change without notice.

Copyright 2018 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd.

All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

www.unitechbarcode.com Unitech America | info@us.ute.com | (800) 861. 8648

HF/NFC

Frequency 13.56Mhz Support: ISO14443A/B, ISO15693 standard, Supports NFC

1.4GHz, Qualcomm 8937 Octa-Core

Enhanced security by preventing 3rd party data

Input Chinese/ English, supports handwriting

gloves and supports wet resistance.

SOTI, 12Manage, and MoboLink

All major 1D and 2D codes

Rechargeable and swappable

environment)

Real time clock battery

3.8 V, 4000mAh Polymer Li-ION pack.

10-12 hours (depending on the specific

5.0 inch TFT-LCD HD (720 x 1280) color screen,

Ultra sensitive capacitive touch screen, compatible with

Side scan button x 2 (left / right), User-defined function

(programmable key), volume switch button (+ / -), ON

2 GB LPDDR3 RAM

collection (without GMS).

16 GB ROM Android 7.1

Multi-language

and soft keyboard.

Gorilla Glass 3.

button

/ OFF button.

Power Source

Main battery

Operation time

RTC battery

Audio

Enclosure Weight

Dimensions

Microphone, speaker and 3.5mm audio jack

10 oz (283g) 6" x 3.1" x 0.6" (152 mm x 78 mm x 15 mm)

Communication Camera and flashlight

External storage USB

WIAN Bluetooth WWAN

Pogo Pin OTG Sensors Indicator