



PolyPro 3000T Clear

Permanent labels

Thermal Transfer

Description

A topcoated gloss polypropylene film with a general purpose permanent acrylic adhesive. Produces good quality text and barcodes using Zebra resin ribbons. The product has good durability and scratch resistance, when using 4800 or 5095 resin ribbon. Product is supplied with a general purpose acrylic based adhesive with good adhesion to a variety of surfaces.

Note: Due to label transparency, bar code scannability depends on substrate colour. Customers should test all bar code applications for acceptable print contrast signal (PCS).

Suggested Applications

- Promotional labelling
- Document labelling
- For use as a protective over-laminate

Technical Specifications

	Description	Caliper
Facestock	Gloss clear polypropylene film	59 microns
Adhesive	Acrylic based, permanent adhesive	15 microns
Liner	61gsm Glassine liner	56 microns
	Total	130 microns

Recommended Zebra printers: mid-range and high-performance thermal transfer printers

Recommended Zebra ribbons: 4800, 5095

Minimum application temperature: 5°C

Service temperature range: -20°C to 80°C

Recommended storage conditions: One year duration when stored at approx 20C 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order SAM65036.