



PolyPro 4000T Matte

Permanent labels

Thermal Transfer

Description

A matt top coated, biaxially-oriented white polypropylene thermal transfer label stock with excellent ink receptivity, coated specially for use with Zebra 3200, 4800 and 5095 thermal transfer ribbons to produce outstanding print quality. High quality permanent acrylic adhesive offers superior performance and is compatible with a wide variety of surfaces and temperature ranges. This material meets FDA standard 175.105 for indirect food contact requirements.

Suggested Applications

- Labelling of most packaging materials, especially corrugate, plastic, glass and metal
- Industrial product labelling in chemical, medical, food and drug industries
- Capital asset labelling
- Applications requiring superior resistance to oil, alcohol, dirt, blood and water

Technical Specifications

	Description	Caliper
Facestock	white topcoated polypropylene film	75 microns
Adhesive	Acrylic based, permanent adhesive	20 microns
Liner	64gsm Glassine liner	56 microns
	Total	151 microns

Recommended Zebra printers: mid-range and high-performance thermal transfer printers

Recommended Zebra ribbons: 3200, 4800, 5095

Minimum application temperature: 10°C

Service temperature range: -40°C to 80°C

Recommended storage conditions: One year duration when stored at approx 20C 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order SAM5137.