



HT682LR (Long Range)

Advanced reading performance

The Unitech HT682LR (Long Range) is a high quality handheld terminal offering great features and amazing reading performance. Equipped with a high performance omnidirectional 2D Near-Far area imager, the HT682LR gives you the reliability and flexibility needed to increase productivity and efficiency in all of your data collection applications.

Designed for the toughest work environments, this device is suitable for a wide range of applications, especially in retail, warehousing and logistics.

The HT682LR offers advanced performance at an affordable price!

Advanced performance and durable design

Equipped with a fast 800 MHz processor and Microsoft Windows Embedded CE 6.0 operating system makes this device not only fast but also compatible with a variety of existing software applications. Its Bluetooth and WiFi (802.11 a/b/g/n) provide fast real-time data collection.

Conform to Unitech standards, the HT682LR is ultra-rugged and designed for the toughest working environments. The HT682LR is IP65 rated, can withstand a multiple 1.8 meter drop to concrete and features golden plated non-rusting connector pins.

High performance long range imager

The HT682LR offers advanced reading performance in terms of accuracy, flexibility and distance. With a long range reading distance of 4 to 5 meters, this long range 2D area imager makes scanning more efficient since there is no need to step out of your forklift truck.

Extended usage

The HT682LR weighs only 381g and is ergonomically designed for one-handed operation and 30° tilted helical scanning. The optional gun grip and extended battery makes the HT682LR perfect for scan-intensive applications. Equipped with a built-in VT terminal emulation and 12Manage (Remote Device Management) supported makes the HT682LR perfect for extended usage!

Reading distance up to 5 meters!

Main Features

- Microsoft Windows Embedded CE 6.0
- TI OMAP AM3703, 800MHz CPU
- Omnidirectional Long-range 2D imager (reading distance up to 5 meters)
- 30 degree scanning tilt
- Gold plated non-rusting connector pins
- IP65 rated and 1.8 meter drop test to concrete
- Built-in VT terminal emulation and 12Manage supported



unitech
because we care

HT682LR

Specifications

Operation System

CPU	TI OMAP AM3703, 800MHz
Memory	SDRAM : 512MB Flash ROM : 512MB
OS	Microsoft Windows Embedded CE 6.0

Display

2.8" QVGA, Color Transflective TFT, with Touch Screen & backlight

Keypad

22 Keys, including 4-direction, function and numeric keys

Indicator

LEDs, Vibrator

Integrated reading devices

HT682LR: Omnidirectional Near-Far 2D imager

Symbologies

1D:

EAN/UPC, GS1 Databar (limited expanded & omni-directional), RSS, Code 39, Code 128, UCC/EAN 128, ISBN, ISBT, Interleaved/Matrix/Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen, postal codes (Australian Post, BPO, Canada Post, Dutch Post, Japan Post, PostNet, Sweden Post).

2D:

Data Matrix, PDF417, Micro PDF 417, Codablock, Maxicode, QR, Aztec, GS1 composite codes

Power Source

Main battery	8.14 Watt-Hour	3.7V@2200 mAh
Backup battery	14.8 Watt-Hour	3.7V@4000 mAh backup capability over 72 hrs

Communication

USB	USB V2.0 Client, Host
WLAN	CCXv4 certified Summit Radio 802.11 a/b/g/n WEP, WPA, WPA2, WEP, RC4 Algorithm. TKIP, RC4 Algorithm, AES, Rijndael Algorithm, Static (40-bit and 128-bit lengths), Pre-Shared (PSK), Dynamic EAP- FAST, EAP-TLS, EAP-TTLS, PEAP-GTC
Bluetooth	Bluetooth 2.1 + EDR

Audio

Speaker	Mono speaker, 90dB at 10 cm distance
---------	--------------------------------------

Enclosure

Weight	381g
Dimension	Approximately 170mm x 55mm x 30mm

Expansion Slot

Micro SD Support SDHC up to 32GB

Environmental

Operating temperature	-10°C to 50°C
Storage temperature	-20°C to 60°C
Relative Humidity	5% ~ 95% (non-condensing)
Drop Specification	1.8 meter (drop test to concrete)
Environmental Sealing	IP65

Software

Unitech Handheld terminal SDK

12Manage & 12Solutions



In-house developed software to enhance device deployment and remote management. 12[want:to]Solutions including 12Manage improve system reliability, reduce service costs and ensure systems running smoothly.

More info: 12manage.unitech.eu or portal.unitech.eu.

Accessories

Gun grip
Leather Case
Single Slot USB Cradle
4-Slot battery charger
2200mAh standard battery
Battery door for standard battery
4000mAh double battery pack
USB communication and charging cable
Power adaptor with universal plugs



Standard battery
excl. battery door



Battery door
for standard battery



Double battery
incl. battery door



Gun grip
incl. battery

Regulatory Approvals

CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance



Unitech's service program

UnitCare offers customers a high level of security by a reliable, high-quality and effective program for getting your devices serviced quickly. It also drives the hidden costs out of your installations. UnitCare goes beyond the standard warranty with a complete service offer for different need.

More information: unitcare.unitech.eu

Unitech Europe

Tilburg, The Netherlands
• Tel.: +31 (0)13 460 9292
• Email: Info@eu.ute.com
• Website: <http://eu.ute.com>



unitech
because we care

Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan