

## RFID Keyfob SAIL

iDTRONIC RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal key ring. They are available with the most common ICs in 125kHz as well as in 13,56MHz.

The keyfob SAIL comes in an attractive semi-transparent housing which give you a view on the RFID unit inside.



### Applications:

- Access Control
- Identification
- Time Attendance
- Health Clubs

### Personalisation options:

- Laser Engraved number

### Product specification:

<b>Dimensions:</b>	55 x 32 x 8mm
<b>Weight:</b>	7g
<b>Material:</b>	Polycarbonat
<b>Colours:</b>	grey, blue, red
<b>Surface:</b>	opac
<b>Humidity resistance:</b>	IP 67
<b>Application temp.:</b>	- 25°C to 65°C

### Available 125kHz systems:

IC Type	Memory	Mode
EM 4100/4200	8 byte	Read Only
EM 4450/4550	125 byte	R/W
Atmel Temic 5567	28 byte	R/W
NXP Hitag1	256 byte	R/W
NXP Hitag2	32 byte	R/W
NXP HitagS	64 / 256 byte	R/W

### Available 13,56MHz systems:

IC Type	ISO	Memory
NXP Mifare Ultralight	14443A	64 byte
NXP Mifare MF1S50	14443A	1024 byte
NXP Mifare MF1S70	14443A	1024 byte
NXP Mifare DESFire EV1	14443A	-
NXP I-Code SLI	15693	64 byte
NXP I-Code SLI-S	15693	256 byte
LEGIC MIM256	-	256 byte
LEGIC MIM1024	-	1024byte